
LUX PROFFS B5010 EI60	570 x 800 mm	Fire rate EI60
LUX PROFFS B5020 EI60	570 x 1100 mm	Fire rate EI60

Casing:

<u>outer size</u>	<u>inner size</u>	<u>size including architrave</u>	<u>opening in the ceiling</u>
570 x 800 mm	490 x 720 mm	680 x 910 mm	590 x 820 mm
570 x 1100 mm	490 x 1020 mm	680 x 1210 mm	590 x 1120 mm

The steel casing has the measurement 103,5 x 95 x 1,5 mm and is manufactured with the integrated architrave.

Trap door:

Trap door	steel, 1,25 mm on both sides.
Insulation	50 mm mineral wool 140kg/m ³
Insulation factor B5010	0.51 W/m ² C ^o
Insulation factor B5020	0.51 W/m ² C ^o

Surface treatment:

Gray prime

Fire rate:

EI60 according to the Swedish Construction Norms.

Locking:

Lock	Assa Ruko 1498 symmetric, can be ordered prepared for cylinder locking
Key/Handle	round iron with diameter 9 mm, length 120 mm
Measurement	square 7-8 mm.

Sealing:

V formed seal is mounted between the trapdoor and the casing.

Others:

The hinges on the hatch are placed against each other which make it possible to place the door either on the right or the left side.

Note!!! The wall hatch is not allowed to be used on the ceiling.

Weight

product	weight	units per pallet
LUXPROFFS B5010	22 kg	6
LUXPROFFS B5020	31 kg	6